



DP-4"



T+RH+DP+ TIME - 4"



T+RH - 4"



T+RH+DP+ TIME - 7"

MULTI. COMMU.
SUPPORTED
MODBUS(232/485),
ETHERNET,WIFI,
WIRELESS(RF,
BLUETOOTH)

7" / 4" MULTI COLOUR
GRAPHICAL
TOUCH SCREEN,
4-GB IN BUILT
MEMORY WITH
2 YEAR DATA
BACKUP

Built Memory
Automatic
Data Back
Filing Facility

BUILT IN /
REMOTE
DIGITAL
SENSOR FOR
T+RH+DP

SENSOR

SYNCHRONIZE
SLAVE TIME
WITH
CALENDERS &
RTC.

CLOCK

BUILT IN AHU
ON / OFF / TRIP
DISPLAY WITH
DIGITAL
INPUTS.

DIGITAL INPUT

CLEAN ROOM DISPLAY [EMS/BEMS]

FEATURE :

- Micro controller based indicator with inbuilt Temp., RH & DP measurement.
- All channel are programmable ranges and unit.(Through Front key pad).
- Incorporates highly stable built-in Temp + RH + DP sensor.
- 4 " / 7 " Touch TFT LCD Display for displaying DP, RH , Temperature & Time.
- Process parameter High and Low Status indication For All three channel.
- Built in Memory for Automatic Data Back Filing Facility.-
- Inbuilt buzzer to audible process value violation.
- 3 Level Password protection for calibration and programming mode.
- Compact, All Stainless Steel enclosure with 35 mm depth for installation in prefab panels.
- Different communication Protocol Available Like : Rs 485/232 / Ethernet / Wi-Fi / Wireless

UT-1420 - 1

Display Size	
Touch 4 Inch	4
Touch 7 Inch	7

2

Instrument type	
T+RH	1
DP	2
T+RH+DP	3
T+RH+DP	4

3

Sensor Type	
INTEGRAL	I
REMOTE	R

4

Aux power	
230V AC	2
110V AC	1
24V DC	4

5

TIMR	
None	N
TIME	2

6

Comm.	
None	N
RS-232	2
RS-485	4
ETHERNET	E





PROCESS INDICATOR & CONTROLLERS



Data Loggers and Scanners



COMMUNICATION CONVERTORS



FLAME PROOF INDICATOR AND PANELS



FLOW INDICATOR CUM TOTALIZER & CONTR.



Other Product



SIGNAL ISOLATOR & TRANSMITTERS



PROCESS INDICATOR & CONTROLLERS



CLEAN ROOM INSTRUMENTS- PHARMA

